



Waxman Ceramics



FLAGSTONE

Glazed Porcelain Tiles



COLOURS



Bianco
48x96cm



Bianco
48x48cm



Bianco
32x48cm



Bianco
32x32cm



= Anti-Slip

Slip Resistance		
	R9	+36

COLOURS



Grigio
48x96cm



Grigio
48x48cm



Grigio
32x48cm



Grigio
32x32cm



= Anti-Slip

Slip Resistance		
	R9	+36

COLOURS



Nero
48x96cm



Nero
48x48cm



Nero
32x48cm



Nero
32x32cm



A = Anti-Slip

Slip Resistance		
	R9	+36

COLOURS



Ruggine
48x96cm



Ruggine
48x48cm



Ruggine
32x48cm



Ruggine
32x32cm



A = Anti-Slip		
Slip Resistance		
	R9	+36

MULTISIZE LAYING SUGGESTIONS



Suggested 3 Size Mix
2 x 32x32cm
2 x 32x48cm
2 x 48x48cm
0.97m²



Suggested 4 Size Mix
4 x 32x32cm
4 x 32x48cm
4 x 48x48cm
1 x 48x96cm
2.41m²



Bianco - 48x96cm / Bianco - 48x48cm / Bianco - 32x48cm



Grigio - 48x96cm



Nero - 48x96cm / Nero - 48x48cm / Nero - 32x48cm / Nero - 32x32cm



Nero - 48x96cm / Nero - 48x48cm / Nero - 32x48cm / Nero - 32x32cm



Ruggine - 48x96cm / Ruggine - 48x48cm



Ruggine - 48x48cm

SPECIFICATION & PACKING

Glazed Porcelain Tiles

Suitability	Thickness	Walls		Floors		Frostproof	Colour Variation
		Internal	External	Internal	External		
48x96cm	10mm	✓	✓	✓		Yes	V2
48x48cm	10mm	✓	✓	✓		Yes	V2
32x48cm	10mm	✓	✓	✓		Yes	V2
32x32cm	10mm	✓	✓	✓		Yes	V2

Packing	Pcs / ctn	M ² / Ctn	Kg / Ctn	Ctns / Pallet	M ² / Pallet
48x96cm	2	0.93	19.74	42	39.06
48x48cm	6	1.38	30.70	24	33.12
32x48cm	8	1.23	27.40	36	44.28
32x32cm	12	1.23	24.48	42	51.66

Waxman Ceramics

Head Office **01422 311331**

Grove Mills
Elland
West Yorkshire
HX5 9DZ
England

Email info@waxmanceramics.co.uk
Web www.waxmanceramics.co.uk

Waxman Ceramics Ltd - Part of the Waxman Group

The information contained within this document is, to the best of our knowledge, accurate at the time of production.
We reserve the right to modify this document at any time.
Whilst every attempt has been made to accurately reproduce colours and textures, images used within this document are only intended as a guide.
Please refer to actual product samples before specifying or ordering.

REF: 19/03